Mathematics for New Technologies in Finance

Exercise sheet 8

Through this exercise sheet, we let $E = \mathbb{R}^d$, J an interval on $\mathbb{R}$, and denote $\mathbf{Sig}_J \colon \mathcal{C}_0^1(J, E) \to \mathbf{T}(E)$ the signature map such that for all $X \in \mathcal{C}_0^1(J, E)$.

Exercise 8.1 (Signatures and reservoirs computing)

(a) Let $X \in \mathcal{C}_0^1([0, T], \mathbb{R}^n)$ satisfying the dynamic:

$$dX_t = \sum_{k=1}^{m} V_k(X_t) dW_t^k, \quad X_t \in \mathbb{R}^n, W_t \in \mathbb{R}^m, V^k \colon \mathbb{R}^n \to \mathbb{R}^n, \tag{1}$$

where $(W_t)_{t=0}^{\infty}$ is a Brownian motion. Prove that

$$X_t = \sum_{d=0}^{\infty} \sum_{i_1, \cdots, i_d = 1}^{n} \left(\int_{0 \le t_1 \le \cdots \le t_d \le t} dW_{t_1}^{i_1} \cdots dW_{t_d}^{i_d} \right) V^{i_d} \cdots V^{i_1}(X_0) \cdot X_0. \tag{2}$$

where

$$Vf(x) = df(x) \cdot V(x).$$

(b) Rewrite (2) with signature in the form of the following:

$$X_t = \langle \mathbf{R}, \mathbf{Sig}_{[0,t]}(W) \rangle X_0, \tag{3}$$

and express the readout $\mathbf{R}$ with $(V^k)_{k=1}^m$ (notice that $\mathbf{R}$ depends on X_0).

(c) Relate (3) with reservoirs computing.

Exercise 8.2 In Exercise 8.1, denote the dimension of state space by N and the number of Brownian motion by d

(a) Choose a dimension N and some random matrices $A_1, \ldots, A_d$, then consider the Taylor expansion. Look at the solution of this system and describe their relation to signature. Can we express all signature components from this system?

(b) Choose a dimension N and some random NN vector fields of type $\sigma(A_1 . + b_1), \ldots, \sigma(A_d . + b_d)$. Consider a learning task $u \mapsto \sup(u(.))$ and solve the regression problem on path space (Lipschitz functions) by a regression.

References

[1] Ilya Chevyrev and Andrey Kormilitzin. A primer on the signature method in machine learning. *arXiv preprint arXiv:1603.03788*, 2016.

[2] Terry J Lyons, Michael Caruana, and Thierry Lévy. *Differential equations driven by rough paths.* Springer, 2007.